

# Sensor Deck Mounted Soap Dispenser


TSL.420


The TSL.420 is a stainless steel deck mounted soap dispenser, available in a variety of coloured finishes, with a sleep minimalist design.

Finish	Codes	LRV*
<ul><li>Satin</li></ul>	TSL.420.CS	58
<ul><li>Black</li></ul>	TSL.420.BK	3
<ul><li>Brass</li></ul>	TSL.420.BR	40
<ul><li>Copper</li></ul>	TSL.420.CP	19
<ul><li>Bronze</li></ul>	TSL.420.BZ	17
Chrome	TSL.420.C	75

<sup>\*</sup>Light reflectance value













REV 2025 29-Aug UK: +44 (0) 161 482 7000 www.thesplashlab.com/uk info.uk@thesplashlab.com All things considered.

#### **Technical Data**

Weight	1KG	
Material	AISI 304 Stainless Steel	
Power supply	110V - 230V ac; 50/60Hz	
Output	1000mA	
Standby power	O.1W	
Standard discharge	1.Oml	
Coating type	PVD (colours only)	
Max hot water temperature	60°C	
Recommended soap type	Foam soap - <10cPS viscosity. Not suitable for liquid soaps, alcohol gels or hand sanitisers	
Soap reservoir capacity	1 Litre (standard) 5 Litres (optimal remote feed)	
Sensor range	Preset 70mm (adjustable using separate controller if required) Max range 400mm Min range 60mm	
Sensor type	Infrared	
Response time (max)	< 300ms	
Security cut-off time	30 seconds	
Cable length	Connection to sensor cable - 700mm Connection to fused supply - 2m	

## Installation requirments

Countertop cut-out size	Ø25mm	
Maximum countertop thickness	50mm	
Access requirements	Power supply units and pump units must be accessbile at for initial installation & commissioning for ongoing/routine maintenance	
Washroom layout	Soap pump and reservoir must be accessible for installation, commissioning and on going maintenance.	
Power supply	3amp fused spur to be connected to IP68 transformer supplied; low voltage push fit connector to dispenser. It is not recommended that sensor-operated soap dispenser are connected to an occupancy circuit.	

REV 2025 29-Aug UK: +44 (0) 161 482 7000 www.thesplashlab.com/uk info.uk@thesplashlab.com All things considered.


#### Included

Soap Foamer TSLP.230326

IR Sensor Soap TSLP.260013

Foamer Pick-up Pipe LSTB

1.5L Soap Tank - (No Handle) TSL.230327



# Warranty & Spare parts

For warranty terms and conditions please visit www.thesplashlab.com

If additional spare parts are required and are not listed below, please contact us at info.uk@thesplashlab.com

## Related products



Radius Auspex Tap 150mm TSL.895



Radius Auspex Tap 220mm TSL.894



Wall Mounted Manual Soap Dispenser TSL.470