

# **Sensor Deck Mounted Soap Dispenser**

TSL.420

The TSL.420 is a stainless steel deck mounted soap dispenser, available in a variety of coloured finishes, with a sleek minimalist design.

Finish	Codes	LRV*
Satin	TSL.420.CS	58
Black	TSL.420.BK	3
Brass	TSL.420.BR	40
Copper	TSL.420.CP	19
Chrome	TSL.420.C	75

Light Reflectance Value\*

<sup>+</sup>Satin





<sup>+</sup> Black





<sup>+</sup> Chrome




#### **Technical Data**

Weight	1Kg	
Material	AISI 304 Stainless Steel	
Power supply	110V - 230V ac; 50/60Hz	
Output	1000mA	
Standby power	O.1W	
Standard discharge	1.Oml	
Coating type	PVD (colours only)	
Max hot water temperature	60°C	
Recommended soap type	Foam soap - <10cPS viscosity. Not suitable for liquid soaps, alcohol gels or hand sanitisers	
Soap reservoir capacity	1 Litre (standard) 5 Litres (optional remote feed)	
Sensor range	Preset 70mm (adjustable using separate controller if required) Max range 400mm Min range 60mm	
Sensor type	Infrared	
Response time (max)	< 300ms	
Security cut-off time	30 seconds	
Cable lengths	Connection to sensor cable - 700mm Connection to fused supply - 2m	

## Installation requirments

Countertop cut-out size	ø 25mm	
Maximum countertop thickness	50mm	
Access requirements	Power supply units and pump units must be accessible for initial installation & commissioning for ongoing/routine maintenance.	
Power supply	Samp fused spur to be connected to IP68 transformer supplied; low voltage push fit connector to dispenser. It is not recommended that sensor-operated soap dispenser are connected to an occupancy circuit.	



### Warranty & Spare Parts

For warranty terms and conditions please visit www.thesplashlab.com If additional spare parts are required and are not listed above, please contact us at info.uk@thesplashlab.com

#### **Related products**



Aromatherapy Foam Soap TSL.AFS



Sensor Deck Mounted Tap/Small

TSL.990





Sensor Deck Mounted Tap/Large TSL.960

Deck Mounted Soap Dispenser TSL.410