

TSL.410

Deck mounted
 soap dispenser

The TSL.410 is a stainless steel deck mounted soap dispenser, available in a variety of coloured finishes with a sleek and minimalist design.



CODES	FINISHES	LIGHT REFLECTANCE VALUE (LRV)
TSL.410.CS	Brushed Stainless Steel	58

RELATED DOCUMENTS

Installation and maintenance manual	email: technical@thesplashlab.com
Warranty document	email: technical@thesplashlab.com

WARRANTY

Warranty	2 years from date of purchase
----------	-------------------------------

RELATED PRODUCTS

Soap Dispenser	TSL.410 Manual soap dispenser TSL.420 Sensor operated soap dispenser
----------------	---

TECHNICAL DATA

Weight	700g
Material	AISI 304 Stainless Steel
Pump Type	Manual piston-type
Standard Discharge	1.0ml
Coating Type	PVD (colours only)
Max hot water temperature	60°C
Recommended soap type	Liquid soap - <100 - 3800cPS viscosity. Not suitable for foam soaps, alcohol gels or hand sanitisers.
Soap Reservoir Capacity	1 Litre (standard) 5 Litres (optional remote feed)

RELATED PRODUCTS

Soap Feed Systems	LST1 - 5L reservoir with 2m feed pipe LST2 - 5L reservoir with 2x 2m feed pipe LST3 - 5L reservoir with 3x 2m feed pipe LST4 - 5L reservoir with 4x 2m feed pipe
Sensor Operated Taps	TSL.940 Wall mounted tap TSL.960 Wall mounted tap TSL.980 Wall mounted tap TSL.990 Wall mounted tap

COMPLIANCE

WRAS	Pending
CE	PSU conforms to RoHS, REACH, EN15091
BREEAM	Qualifies for up to 5 credits as part of water efficiency assessment

INSTALLATION REQUIREMENTS

Countertop Cut-out Size	Ø 25mm
Maximum Countertop Thickness	50mm
Access Requirements	Soap reservoir must be accessible at for initial installation & commissioning and for ongoing/routine maintenance.
Washroom Layout	Reservoir must be accessible for installation, commissioning and ongoing maintenance.

TECHNICAL DRAWING

