

Exposed Shower

TSL.SHW.002

A minimalist stainless steel shower assembly with handheld flow, offered in four PVD colours as well as brushed satin. Exposed assembly design for installation on finished walls.

Finish	Codes	LRV*
● Satin	TSL.SHW.002.CS	3
● Black	TSL.SHW.002.BK	40
● Brass	TSL.SHW.002.BR	58
● Copper	TSL.SHW.002.CP	17
● Bronze	TSL.SHW.002.BZ	19

*Light reflectance value

+ Satin



+ Black



+ Brass



+ Copper



+ Bronze



Technical Data – Shower Head

Body material	AISI304 Stainless steel
Coating Type	PVD (colours only)
Minimum Pressure	1 Bar
Maximum Pressure	10 Bar
Recommended Working Pressure	2-5 Bar
Maximum Water Temperature	70°C / 176 F
Maximum Recommended Water Temperature	65°C / 149 F
Flow Rates	Flow rate: 12L/pm standard - 6L/pm , 8L/pm & 9L/pm optional available

Technical Data – Handset

Body material	AISI304 Stainless steel
Coating Type	PVD (colours only)
Minimum Pressure	1 Bar
Maximum Pressure	10 Bar
Recommended Working Pressure	2-5 Bar
Maximum Water Temperature	70°C / 176 F
Maximum Recommended Water Temperature	65°C / 149 F
Flow Rates	Flow rate: 12L/pm standard - 6L/pm , 8L/pm & 9L/pm optional available

Exposed Shower
TSL.SHW.002

Technical drawing of the shower set showing front and side views with dimensions.

FRONT

Dimensions (mm):

- Shower head diameter: $\varnothing 200$
- Shower head height from wall: 20.5
- Shower head height from floor: 18.4
- Shower head height from floor (total): 1009.5
- Shower head height from floor (total): 286
- Shower head height from floor (total): 150
- Shower head height from floor (total): 45

SIDE

Dimensions (mm):

- Shower head height from wall: 519.5
- Shower head height from wall: 419.5
- Shower head height from floor: 1009.5

For warranty terms and conditions please visit www.thesplashlab.com

If additional spare parts are required and are not listed below, please contact us at info.uk@thesplashlab.com

Wall Mounted Manual Tap

TSL.970



Radius Auspex 150mm
TSL.895

Concealed Shower
TSL.SHW.001