



Exposed Shower

TSL.SHW.002

A minimalist stainless steel shower assembly with handheld flow, offered in four PVD colours as well as brushed satin. Exposed assembly design for installation on finished walls.

Finish	Codes	LRV*
● Satin	TSL.SHW.002.CS	3
● Black	TSL.SHW.002.BK	40
● Brass	TSL.SHW.002.BR	58
● Copper	TSL.SHW.002.CP	17
● Bronze	TSL.SHW.002.BZ	19

*Light reflectance value



Technical Data - Shower Head

Body material	AISI304 Stainless steel
Coating Type	PVD (colours only)
Minimum Pressure	1 Bar
Maximum Pressure	10 Bar
Recommended Working Pressure	2-5 Bar
Maximum Water Temperature	70°C / 176 F
Maximum Recommended Water Temperature	65°C / 149 F
Flow Rates	12 L/min - 3 Bar 6L/min - 3 Bar

Technical Data - Handset

Body material	AISI304 Stainless steel
Coating Type	PVD (colours only)
Minimum Pressure	1 Bar
Maximum Pressure	10 Bar
Recommended Working Pressure	2-5 Bar
Maximum Water Temperature	70°C / 176 F
Maximum Recommended Water Temperature	65°C / 149 F
Flow Rates	12 L/min - 3 Bar 6L/min - 3 Bar

Exposed Shower
TSL.SHW.002

Technical drawing of the shower set showing front and side views with dimensions.

FRONT

Dimensions (mm):

- Shower head diameter: $\varnothing 200$
- Shower head offset: 20.5
- Height from wall to shower head center: 184
- Height from wall to control panel center: 150
- Control panel width: 45
- Base width: 286

SIDE

Dimensions (mm):

- Shower head offset: 519.5
- Shower head offset: 419.5
- Height from wall to control panel center: 1009.5

A perspective view of the shower set is shown on the right side of the page.

If additional spare parts are required and are not listed below, please contact us at info.uk@thesplashlab.com

REV 2025 2-Jul

Additional views

A	Setting out
B	Installation

