



# Exposed Shower

TSL.SHW.002

A minimalist stainless steel shower assembly with handheld flow, offered in four PVD colours as well as brushed satin. Exposed assembly design for installation on finished walls.

Finish	Codes	LRV*
● Satin	TSL.SHW.002.CS	3
● Black	TSL.SHW.002.BK	40
● Brass	TSL.SHW.002.BR	58
● Copper	TSL.SHW.002.CP	17
● Bronze	TSL.SHW.002.BZ	19

\*Light reflectance value



**Technical Data - Shower Head**

Body material	AISI304 Stainless steel
Coating Type	PVD (colours only)
Minimum Pressure	1 Bar
Maximum Pressure	10 Bar
Recommended Working Pressure	2-5 Bar
Maximum Water Temperature	70°C / 176 F
Maximum Recommended Water Temperature	65°C / 149 F
Flow Rates	Flow rate: 12L/pm standard - 6L/pm , 8L/pm & 9L/pm optional available

**Technical Data - Handset**

Body material	AISI304 Stainless steel
Coating Type	PVD (colours only)
Minimum Pressure	1 Bar
Maximum Pressure	10 Bar
Recommended Working Pressure	2-5 Bar
Maximum Water Temperature	70°C / 176 F
Maximum Recommended Water Temperature	65°C / 149 F
Flow Rates	Flow rate: 12L/pm standard - 6L/pm , 8L/pm & 9L/pm optional available

Exposed Shower  
TSL.SHW.002

If additional spare parts are required and are not listed below, please contact us at [info.uk@thesplashlab.com](mailto:info.uk@thesplashlab.com)



REV 2025 29-Aug

Additional views

A	Setting out
B	Installation

