

Recessed Hand Dryer

TSL.LM9

Ultra slim body hand dryer with an overall recessing depth of 4" which will fit into a standard partition wall.

Finish	Codes	LRV*
● Satin	LM9	51
Light Reflectance Value*		




Technical Data

Finishes	CS (Brushed stainless steel)
Stainless steel grade	AISI 304
Voltage	110 – 120V
Frequency	60Hz
Motor power	325 – 500W – adjustable
Heater power	500W – can be switched on / off
Stand-by power	0.3 – 0.4W
Air speed	229 – 269ft/sec – adjustable
Drying time	10 – 15 seconds
Sound level	72.8dB to 77.6dB
Drip proof	IP24
Timing protection	60 seconds auto shut-off
Motor thermal protection	Auto resetting thermostat turns unit off at 275° F
Heater thermal protection	Auto resetting thermostat turn unit off at 185° F\ Thermal fuse cuts unit off at 288° F
Approvals	UL listed File # KSOT. E364850 (L-1000W/11)
Weight	28lb 10oz

Installation requirments

Cutout dimensions	14 1/8 " x 21 5/8 "
Minimum void depth	4"
Fixing	Concealed screws through side flange to solid wall or timber framed aperture, or, internal clamp to solid facing-board.




Included

Combination Unit

Warranty

1 Year parts and labor



Spare parts

If a situation arises where you require replacement components outside of a maintenance contract, there may be provision to obtain spare parts. Providing the components are under warranty and the parts have become non-functioning during normal use within their assumed usable life, they may be replaced. Should a replacement mains power supply be required it is imperative that an identical type is used. Contact **The Splash Lab** for further information.

Related products



Combination Unit
TSL.LM11



Combination Unit
TSL.LM8