

TSL.R.030

Ribbon Dryer

With an acoustically insulated and powerful blower unit, the Ribbon Hand Dryer offers a quiet user experience with fast and efficient drying times. Furthermore, with a touch free sink mounted system, there are no longer any drips carried across your washroom floors.



CODES	POWER SUPPLY	FINISH	LIGHT REFLECTANCE VALUE
TSL.R.030.C.E230	230V	Bright Polished Stainless steel	58
TSL.R.030.CS.E230	230V	Brushed Stainless steel	51

TECHNICAL DATA

Voltage	220 - 240V ac; 50Hz
Current	3.8 - 4.2A
Power consumption	0.84 - 1.0kW
Standby power	0.3 - 0.4W
Drying time	<15 seconds
Weight	8.1kg
Material	AISI 304 stainless steel
Noise levels	70.6dB
Heating element	500W
Motor type	Brush type; dual ball bearings
Motor power	500 - 350W
Air speed	112 m/s
Air flow	43m ³ /hr

TECHNICAL DATA

Sensor range	130mm +/- 20mm
Security cut-off time	30 seconds
Motor thermal protection	Auto resetting thermostat set at 95°C
Heater thermal protection	Auto resetting thermostat set at 85°C Thermal cutout fuse set to 142°C
Insulation	Class 1
IP rating	IP35
Approvals	CE, UL, RoHS
Warranty	1 year parts and labour; additional 4 years parts only (Motor brushes excluded as these are a wearing part, and dependent on usage)

INSTALLATION REQUIREMENTS

Counter-top cut-out (dia)	Ø32mm (1 17/64")
Maximum countertop thickness	35mm (1 3/8")
Anti-rotation collar	included
Reflective surfaces	Not to be installed above highly polished basins
Access requirements	Motor to be accessible at all times for servicing
Cabling	13 amp fused spur
Power supply	It is recommended that the sensors are installed on their own circuit to avoid interference from other power demands. (i.e lighting)

COMPLIANCE

UL approved
Approvals pending for use in UK, USA, Sweden, Denmark

RELATED PRODUCTS

Ribbon soap dispenser	TSL.R.010
Ribbon tap	TSL.R.020

TECHNICAL DRAWING

