

TSL.CO41

**Channel Soap
Dispenser**

Fully compatible with the The Splash Lab Soap Refill System, the automatic foaming nozzle reliably produces a precise dose of soap every time. The system is easily maintained, with the foaming nozzle simple and quick to replace.



<u>CODES</u>	<u>POWER SUPPLY</u>	<u>FINISH</u>	<u>LIGHT REFLECTANCE VALUE</u>
TSL.CO41.C	Mains	Bright Polished	58
TSL.CO41.CS	Mains	Brushed Stainless	51
TSL.CO41.CP	Mains	Brushed Copper	19
TSL.CO41.BK	Mains	Brushed Black	3
TSL.CO41.BR	Mains	Brushed Brass	40

TECHNICAL DATA

Weight	1.5kg
Recommended soap viscosity	Liquid soap:1-3000cPs Foam soap - <10cPs. Not suitable for alcohol gels or hand sanitizers.
Stainless steel grade	316 Stainless steel
Sensor range Preset	70±15mm (Not adjustable)
Power supply - Mains	Input: 100-240V ac; 50/60Hz Output: 6V DC; 1.5A, 9W max
Power supply - Battery	6V Type AA x 4 pcs Alkaline (not included) (Optional)
Standby power	9mA
Warranty	One year limited warranty
Recommended soap system	The Splash Lab automatic soapfeed system

INSTALLATION REQUIREMENTS

Wall cut-out (dia)	Ø22mm
Maximum countertop thickness	35mm
Anti-rotation collar	Included
Reflective surfaces	Not to be installed above highly polished basins
Access requirements	Pumps and transformers must be accessible at all times for servicing
Cabling	Low voltage push fit connector to soap dispenser
Power supply	Hard wired connection to mains branch circuit, It is recommended that the sensors are installed on their own circuit

COMPLIANCE

CE, UKCA, RoHS

RELATED PRODUCTS

Channel tap	TSL.CO51
Channel dryer	TSL.CO61

TECHNICAL DRAWING

