

TSL.CO51

Channel  
Tap

Wall mounted sensor operated tap with robust body construction for all types of projects. Available mains. To be used in conjunction with the Channel dryer and soap dispenser for optimum efficiency.



CODES	POWER SUPPLY	FINISH	LIGHT REFLECTANCE VALUE
TSL.CO51.C	Mains	Bright Polished	58
TSL.CO51.CS	Mains	Brushed Stainless	51
TSL.CO51.CP	Mains	Brushed Copper	19
TSL.CO51.BK	Mains	Brushed Black	3
TSL.CO51.BR	Mains	Brushed Brass	40

**TECHNICAL DATA**

Minimum operating pressure	7 - 87 psi dynamic pressure
Flow rate	0.5 GPM (Other flow rates available upon request)
Weight	1.2kg
Stainless steel grade	316 Stainless steel
Sensor range	Preset 120±20mm (adjustable), Min range 50mm - Max range 150mm
Comfort delay	2 seconds
Security cut-off	60 seconds
Power supply - mains	Input: 100-240V ac; 50/60Hz Output: 6V DC; 0.5A,3W max
Warranty	One year limited warranty

---

#### INSTALLATION REQUIREMENTS

---

Counter-top cut-out (dia)	Ø30mm
Maximum countertop thickness	35mm
Anti-rotation collar	Included
Reflective surfaces	Not to be installed above highly polished basins, or waste outlets
Access requirements	Solenoids and transformers must be accessible at all times for servicing
Cabling	Low voltage push fit connector to tap
Power supply	For the mains power option, it is recommended that the sensors are installed on their own circuit to avoid interference from other power demands.

---

#### COMPLIANCE

---

ASME A112.18.1, CSA B125.1, NSF/ANSI/CAN 61, WRAS, CE, UKCA, RoHS

---

#### RELATED PRODUCTS

---

Channel dryer	TSL.CO61
Channel soap dispenser	TSL.CO41

## TECHNICAL DRAWING

