

TSL.CO61

Channel Dryer

With an acoustically insulated and powerful blower unit, the Channel Hand Dryer offers a quiet user experience with fast and efficient drying times. Furthermore, with a touch free sink mounted system, there are no longer any drips carried across your washroom floors.



CODES	POWER SUPPLY	FINISH	LIGHT REFLECTANCE VALUE
TSL.CO61.C	240V	Bright Polished	58
TSL.CO61.CS	240V	Brushed Stainless	51
TSL.CO61.CP	240V	Brushed Copper	19
TSL.CO61.BK	240V	Brushed Black	3
TSL.CO6.BR	240V	Brushed Brass	40

TECHNICAL DATA

Voltage	220-240V ac; 50/60Hz
Current draw	3.8-4.2A
Power consumption	0.84-1.0kW
Standby power	0.3-0.4W
Drying time	<15 seconds
Weight	8kg
Material	316 Stainless steel
Noise levels	68.6dB
Heating element	500W
Motor type	Brush type; dual ball bearings
Motor power	500-350W
Air speed	93-110 m/s
Air flow	59 m ³ /h

TECHNICAL DATA

Sensor range	120±20 mm
Security cut-off time	60 seconds
Motor thermal protection	Auto resetting thermostat set at 95°C
Heater thermal protection	Auto resetting thermostat set at 85°C
	Thermal cutout fuse set to 142°C
Insulation	Class 1
IP rating	IP35
Approvals	CE, UKCA, RoHS, UL, cUL
Warranty	One year limited warranty
Filter	3M filter assembly (HEPA filter is available for this product, please enquire for technical information)

INSTALLATION REQUIREMENTS

Counter-top cut-out (dia)	Ø30mm
Maximum countertop thickness	35mm
Anti-rotation collar	Included
Reflective surfaces	Not to be installed above highly polished basins
Access requirements	Motor to be accessible at all times for servicing
Cabling	8A fused branch circuit is required
Power supply	It is recommended that the sensors are installed on their own circuit to avoid interference from other power demands. (i.e lighting)

COMPLIANCE

CE, UKCA, RoHS, UL, cUL

RELATED PRODUCTS

Channel soap dispenser	TSL.CO41
Channel tap	TSL.CO51

TECHNICAL DRAWING

